


BREDEL 20 slangepomp

GENERAL INFORMATION

| | |
|--------------|-------------|
| ID | 24P00090 |
| Make | BREDEL |
| Type | slangenpomp |
| Construction | Water pumps |
| Fuel | Electric |
| Weight | 45 kg |
| Power kw | 1 |
| Power hp | 1 |
| Length | 43 cm |
| Width | 46 cm |
| Height | 30 cm |



TECHNICAL INFORMATION

- Can be used immediately • Direction of rotation protection
- in stock! • NEW and UNUSED! • PUMPED UP AND READY TO FLOW! • Pumping water-thin to highly viscous liquids and/or solid components • self-priming (dry) • Unlimited dry running

DESCRIPTION

Damages: none

Bredel peristaltic pumps 20

Bredel peristaltic pumps have no valves or seals to leak, clog or need to be replaced, and deliver flows of up to 17,520 L/h and pressures of up to 16 bar.

They can pump viscous and abrasive slurries, pastes and sludges, with up to 80% solids in suspension.

Unlike other pump types, the highly abrasive nature of grain-filled sludge or stone dust slurry in the water board market does not affect the life of the peristaltic hose pump.

Bredel peristaltic pumps eliminate peripheral equipment such as dry-running protection, seal-water flushing systems and check valves in the pipe. They are also reversible for flushing pipes.

- Dry running and self-priming
- Suction capacity up to 9.5 mwk (354 inWC)
- No seals, check valves, diaphragms, thrust rings, submerged rotors, stators or pistons that could become clogged, leak and corrode, or require replacement
- Suitable for abrasive slurries, corrosive acids, gaseous liquids
- True positive displacement without slippage for accurate,

repeatable dispensing

- No need for peripherals, control valves, seal flushing systems and dry running protection
- Fully reversible flow to safely blow clean suction and discharge lines

If you would like more information, please feel free to contact us.

Throughput capacity: 1 m³/h

Max. head: 100 MWK

Max dirt passag: 90 rpm

Weight: 45 kg