

## PUMPED UP AND READY TO FLOW

# **BREDEL 32 slangenpomp**

### **GENERAL INFORMATION**

ID 24P00089	
Make BREDEL	
Type slangenpomp	
Construction Water pumps	
Fuel Electric	
Weight 130 kg	
Power kw 4	
Power hp 5	
Length 69 cm	
Width 63 cm	
Height 54 cm	



#### **TECHNICAL INFORMATION**

• Can be used immediately • Direction of rotation protection • in stock! • NEW and UNUSED! • PUMPED UP AND READY TO FLOW! • Pumping water-thin to highly viscous liquids and/or solid components • self-priming (dry) • Unlimited dry running

#### DESCRIPTION

#### Damages: none

Bredel peristaltic pumps 32

Bredel peristaltic pumps have no valves or seals to leak, clog or need to be replaced, and deliver flows of up to 17,520 L/h and pressures of up to 16 bar.

They can pump viscous and abrasive slurries, pastes and sludges, with up to 80% solids in suspension.

Unlike other pump types, the highly abrasive nature of grainfilled sludge or stone dust slurry in the water board market does not affect the life of the peristaltic hose pump. Bredel peristaltic pumps eliminate peripheral equipment such as dry-running protection, seal-water flushing systems and check valves in the pipe. They are also reversible for flushing pipes.

- Dry running and self-priming
- Suction capacity up to 9.5 mwk (354 inWC)
- No seals, check valves, diaphragms, thrust rings, submerged rotors, stators or pistons that could become clogged, leak and corrode, or require replacement
  Suitable for abrasive slurries, corrosive acids, gaseous liquids

• True positive displacement without slippage for accurate,

repeatable dispensing

• No need for peripherals, control valves, seal flushing systems and dry running protection

• Fully reversible flow to safely blow clean suction and discharge lines

If you would like more information, please feel free to contact us.

Throughput capacity: 5 m3/h Max. head: 160 MWK Max dirt passag: 140 rpm Weight: 130 kg

Tweelingenlaan 111, 7324 AR Apeldoorn Tel.: +31 (0)55 312 59 02 Email: sales@vantongerentrading.nl