

Selwood S150

GENERAL INFORMATION

Make	Selwood
Year	2011
Operating hours	7.650
Construction	Centrifugal pumps dry priming
Fuel	Diesel
Weight	1.900 kg
Length	245 cm
Width	152 cm
Height	174 cm



TECHNICAL INFORMATION

- 6" (6 inch) connection parts Perrot/Cardan/Type C • available with any desired quick coupling. • Can be used immediately • External fuel connection • Float switch (start/stop system) • Ground switch • in stock! • PUMPED UP AND READY TO FLOW! • Pumping water-thin to highly viscous liquids and/or solid components • self-priming (dry) • Self-priming (dry, vacuum assisted) • Spare parts available, usually in stock • Suitable for pumping bentonite and drilling emulsions • Suitable for pumping sewage • Suitable for pumping surface water / construction site water • SUPER silent housing (SUPER quiet) • Supported by van

DESCRIPTION

Damages: none

The Selwood S150 dirty water pump features a special vortex-flow design, automatic self-priming. Its large dirt passage makes it ideal for heavy-duty work. Bentonite, heavy sandy water and sewage applications are no problem for this powerhouse!

Throughput capacity: 320 m3/h
Max dirt passage: 100 mm
Motor brand: ISUSU
Max. head: 27 MWK
Max dirt passag: 1800 rpm
Weight: 1900 kg